

Kol. Opis

1 Domestic hotwater circulator pump UP 15-14 BA 80



Opozorilo! Slika proizvoda je simbolična

Št. proizvoda: [97680069](#)

Pump with spheric motor for domestic hotwater circulation in single- and two-family houses.

Features and benefits:

- * Unique AUTOADAPT feature saving up to 50% heat energy and 87% motor energy compared with a standard pump in continuous operation
- * Flushing function
- * Automatic legionella eliminating operation (if supported from the system)
- * Automatic weekend and vacation function
- * Temperature control, optional
- * Continuous operation, optional
- * Quick and simple electrical installation due to the highly reliable ALPHA plug
- * Easy-to-clean and lime-insensitive spheric rotor
- * Application range up to 14°dH water hardness
- * Wearless operation due to liquid lubricated bearing
- * No leakage risk due to a static seal
- * Easy maintenance and cleaning through the easy-to-separate pump head fitting all standard circulator pump housings
- * Corrosion resistant brass pump housing
- * No motor protection necessary due to impedance-protected motor
- * No additional installation costs due to integrated non-return and isolating valves in the pump housing.

Tekočina:

Črpana tekočina: Voda
 Razpon temperature tekočine: 2 .. 95 °C
 Temp.tekočine med delovanjem: 60 °C
 Specifična teža: 983.2 kg/m³

Tehnični podatki:

TF razred: 95
 Odobritve na napisni tablici: VDE,BSI,B,CE

Materiali:

Ohišje črpalke: Medenina MS 68
 Tekoč: Nerjaveče jeklo, EPDM, PPO, PTFE, Grafit

Montaža:

Maks. delovni tlak: 10 bar
 Cevni priključek: Rp 1/2

Električni podatki:

Maks. vhodna moč: 25 W

Kol. Opis

Omrežna frekvenca: 50 Hz
Nominalna napetost: 1 x 230 V
Tok pri hitrosti 3: 0.11 A
Velikost kondenzatorja - v teku: 0.6 µF
Razred zaščite (IEC 34-5): IP42
Izolacijski razred (IEC 85): F

Drugo:

Neto teža: 1 kg
Bruto teža: 1.12 kg
Transportni volumen: 0.003 m³