

Kol. Opis

1 SOLOLIFT2 WC-1



Opozorilo! Slika proizvoda je simbolična

Št. proizvoda: [97775314](#)

Sololift2 WC-1 is a small, compact automatic lifting station suitable for pumping of wastewater off places in private dwellings where wastewater cannot be led directly to the sewer by means of a natural downward slope.

Sololift2 WC-1 is suitable for pumping wastewater from a toilet containing toilet paper and faeces with an additional connection on the lid for e.g. a washbasin.

The pumping of liquids containing other material may cause faults and limit the scope of our guarantee.

Sololift2 WC-1 is typically used to dewater:

- toilet and washbasin in basements below sewer level, in connection with the renovation or modernisation of existing buildings, where the location may be remote from the main soil pipe so that a natural slope cannot be established.

The compact lifting station is equipped with

- Cable with or without plug (see technical data)
- Horizontal or vertical fastening possibility of discharge hose connector with several adaptors for pipes with Ø22-40mm

-integrated non return valve

- Dry and high performance motor unit incl. thermal protection, pressure switch and controller
- DN100 toilet connection hose
- Flexible connectors for inlet (adjustable in height) of pipes Ø36 or 40
- Slot for an alarm board with buzzer (accessory)
- Manual anti clogging function and separate drain connection for service
- Venting valve with overflow protection
- Uplift fixation clips

Design according to EN12050-3 and production inspection by external institute with unique features focused on quick installation, long lasting operation and easy clean service.

Note: The discharge adaptor can be mounted vertical or horizontal. Vertical installation increase the flow (s. databooklet and curves)

Tekočina:

Črpana tekočina: Vse Newtonovske tekočine

Maks. temp. medija: 50 °C

Specifična teža: 998.2 kg/m³

Tehnični podatki:

Odobritve na napisni tablici: CE,TR,LGA,VDEEMV,VDE

Toleranca krivulje: ISO9906:2012 3B

Materiali:

Posoda: Plastic

Kol. Opis**Montaža:**

Sesalni priključek črpalke: 32/36/40, DN 100
Tlačni priključek črpalke: 22/25/28/32/36/40
Št. vodnikov: 3X0,75MM2

Električni podatki:

Vhodna moč - P1: 620 W
Omrežna frekvenca: 50 Hz
Nominalna napetost: 1 x 220-240 V
Nominalni tok: 3 A
Cos phi - faktor moči: 0.92
Nominalna hitrost: 2800 rpm
Razred zaščite (IEC 34-5): IP44
Izolacijski razred (IEC 85): F
Dolžina kabla: 1.2 m
Tip kabla: H05VV-F-3G
Tip kabelskega priključka: SCHUKO

Drugo:

Neto teža: 7.95 kg
Bruto teža: 9.55 kg
Danska VVS Številka: 614363432
Švedsko RSK No.: 5886545
Finsko LVI Št.: 4965312
Norveška št. NRF: 9045714
Država izvora: RS
Carin.tarifna št.: 84137021