

Kol. Opis

1 SBA 3-45 AW



Opozorilo! Slika proizvoda je simbolična

Št. proizvoda: [97896312](#)

Grundfos SBA 3-45 AW is an all-in-one submersible booster designed for pumping clean water for domestic use. The SBA is built on the proven SB platform and comes with an integrated control unit. This eliminates the need for an external pump controller in the house. It is silent when submerged and therefore a noiseless alternative to surface-mounted pumps. The pump is built from high quality composite and stainless steel materials that are resistant to corrosion.

The SBA 3-45 AW is equipped with a 15 m supply cable, and the maximum installation depth is 10 m below the water level, with a liquid temperature ranging from 0 °C to 40 °C.

The pump starts automatically when the pipe pressure falls below 2.2 bar.

The SBA 3-45 AW is ideal for operation in a well or ground tanks, as it easily prevents solid particles from entering the pump. The maximum particle size is 1 mm.

The pump features a float switch, which promises the user a convenient experience with automatic start/stop operation of the pump and provides dry running protection.

The pump is equipped with a side inlet/flexible hose with floating suction strainer.

The single-phase model is effectively protected against any accidental overload by built-in thermal protection.

The pump has built-in thermal protection, which immediately stops the pump if it overheats. Having cooled down, the pump automatically restarts when it reaches a normal temperature.

Tekočina:

Črpana tekočina: Voda
Razpon temperature tekočine: 0 .. 40 °C
Temp.tekočine med delovanjem: 20 °C
Specifična teža: 998.2 kg/m³

Tehnični podatki:

Nominalni pretok: 2.83 m³/h
Rated head: 30.1 m
Maks. Delci: 1 mm
Toleranca krivulje: ISO9906:2012 3B
Povratni ventil: YES
Start pressure: 2.4 bar
Nazivna hitrost pogona: 2800 rpm

Kol.	Opis
	Materiali: Ohišje črpalke: Composite Tekač: Composite Montaža: Razpon temperature okolice: -10 .. 50 °C Tip vhodnega priključka: FLOATING STRAINER Tlačni priključek črpalke: G 1" Maks. vgradna globina: 10 m Električni podatki: Izolacija: F Vhod moči P1: 1.05 kW P2: 0.62 kW Omrežna frekvenca: 50 Hz Nominalna napetost: 1 x 220-240 V Cos phi: 0.94 Velikost kondenzatorja - v teku: 13 µF/450 V Razred zaščite (IEC 34-5): IP68 Dolžina kabla: 15 m Tip kabla: H07RN-F 3G1 Tip kabelskega priključka: SCHUKO Nazivni tok: 4.8 A Drugo: Neto teža: 9.83 kg Bruto teža: 10.6 kg Volumen pošiljanja: 0.031 m³ Danska VVS Številka: 391368045 Švedsko RSK No.: 5850423 Finsko LVI Št.: 4822548 Norveška št. NRF: 9041858 Odobritve: CE,VDE,WEEE