

# Triga AN




**Triga AN** 1700↓ × 280↔ ZX  
colour: Soft 7003

Integrated thermostatic valve, angled, left, chrome  
SLIM thermostatic head, chrome  
Integrated pipe-masking set, chrome



**TERMA**  
SINCE 1990






## Standard connection:



## Available sizes:



## Specification:

Working pressure: 1000 kPa    Maximum operating temperature: 95°C


A ↓ [mm]	B ↔ [mm]	C1 [mm]	75/65/20°C [W]	55/45/20°C [W]	D [mm]	E [mm]	F [mm]	 [dm <sup>3</sup> ]	 [kg]	Product code <small>Configuration code p. 5</small>
1700	280	50	953	492	120	1600	50	11,64	22,61	WGVER170028
1900	280	50	1053	548	120	1800	50	12,95	25,03	WGVER190028

# Triga AN



## Technical drawing:



ZX



A – Height B – Width C1-C5 – Distance between pipe centres D – Horizontal distance between mounting bracket centres  
E – Vertical distance between mounting brackets F – Distance between a mounting bracket and the bottom of the radiator

Collector:

Pipe:





In the table with technical data, the last column lists product codes. When placing an order, please remember to quote the product code followed by the configuration code as shown in the diagram below:

## The construction of a water and dual fuel radiator product and configuration code:

WGVER170028

PRODUCT CODE  
(located in the table for the product)

K916ZX

CONFIGURATION CODE  
(supplemented by hand)

### Example Configuration

**K** **916** **ZX**

Package code

*K - carton box*

Colour code

Connection code

## Epoxy primer

**E** - Code of epoxy primer is an extra processes.

WGVER170028 K916ZX **E** — *Extra processes or additions code*

# Triga AN



## Legend



Radiator available in a "water" version.



Radiator suitable for dual fuel connection. Electric heating element can be installed.



Radiator available in electric only version. It comes prefilled with a 'heating medium' and equipped with a heating element. All tested and ready to use.



Connection types dedicated for this radiator. The icon shows the flow and return connections for the radiator as well as the thermostatic valve and heating element position if applicable.



Suggested heating element power output for electric and dual fuel versions.



Weight.



Capacity.



Available in chrome finish.



No additional payment for a color.